

Nitro UK IKONIK Outdoor POE Switch (8 ports + 1 Gibabit uplink port) Spec



Model	Nitro UK IKONIK Outdoor POE Switch (8 ports + 1 uplink port)
chipset	IP1717B
Standard	IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802af, IEEE802.3at
Layer 2 Switching	Backplane Bandwidth: 1.8Gbps Packet Forwarding Speed: 12.96Mbps All Ports Speed Forwarding
Ports	8*10/100m Ethernet Port (PoE) +1*10/100m /1000m uplink port
Power	
Voltage	8* POE port with 802.3at/af standard
Input voltage	AC 100-220V/DC 48V
Power Consumption	4W (standby situation)
Maximum Output Power	13.5W (single port)
MAC Address Table size	4K
Features	IEEE 802.3x traffic control under Full-Duplex mode. Storm control based on the data transmission speed of the port. PPS-based storm control.
VLAN	When the VLAN button in the panel is turned on, 8 POE ports will be isolated from each other but available to communicate with the UPLINK port. When VLAN is off, 9 ports can communicate with each other.
Operating Temperature	-30~60°C
Storage Temperature	-50~80°C
Humidity	≤10~90% (non-condensed)
Product size / Package size	300*220*30 mm / 429*268*94mm
Product weight / Package weight	1.2kg / 1.4kg